

LH-SVS, BH-SVS series

Pressed steel castors, heavy-duty design, with top plate, with extra heavy-duty solid steel wheel



700–900 kg

Bracket: LH/BH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate

Swivel bracket:


- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

Wheel: SVS series

- heat-treatable steel, hardness 190–230 HB, slightly crowned tread

Additional details:

- bracket series: page 92
- wheel series: page 382
- bearing types: page 84–85



Swivel castors	Fixed castors	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LH-SVS 65K	BH-SVS 65K	65	40	700	ball bearing	97	100 x 85	80 x 60	9	45
LH-SVS 80K	BH-SVS 80K	80	40	700	ball bearing	120	100 x 85	80 x 60	9	45
LH-SVS 100K-1	BH-SVS 100K-1	100	40	700	ball bearing	140	100 x 85	80 x 60	9	45
LH-SVS 100K-3	BH-SVS 100K-3	100	40	700	ball bearing	140	140 x 110	105 x 75–80	11	45
LH-SVS 127K	BH-SVS 127K	125	55	900	ball bearing	170	140 x 110	105 x 75–80	11	55

7

Versions / options



	directional lock (separate) 1 x 360°	directional lock (separate) 1 x 360°	directional lock (separate) 1 x 360°	with steel foot guard	truck lock
Technical description page	115	115	115	116	112
Product code suffix	RI-04.01	RI-04.03	RI-05.03	-FS	FF 125
Available for	wheel Ø 80–100 mm with plate 100x85 mm	wheel Ø 100 mm with plate 140x110 mm	wheel Ø 125 mm	wheel Ø 125 mm upon request	wheel Ø 125 mm