

HRLK...-F series

Levelling castors with fixed lock and height-adjustable wheel, with top plate

150 kg

Bracket: HRLK...-F series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- steel truck lock with rubber pad
- height adjustment with swiveling operating lever

Wheel:

- **PO series**
- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour natural white
- **ALTH series**
- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown
- wheel centre: die-cast aluminium

Additional details:

- bracket series: page 100
- wheel series: page 69, 65
- bearing types: page 84–85



Swivel castors	Wheel Ø (D) [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height (H) [mm]	Total height max. (h) [mm]	Stroke (T4) [mm]	Floor clearance foot max. (T3) [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
PO series												
HRLK-PO 80G-F	80	32	150	plain bore	117	122	2	5	100 x 85	80 x 60	9	52
ALTH series												
HRLK-ALTH 80K-F	80	30	150	ball bearing	117	122	2	5	100 x 85	80 x 60	9	52

Versions / options



	image ALTH series	electrically conductive version, wheel non-marking grey	antistatic version, non-marking grey	with top plate 140x110/105x75–80 mm
Technical description page	65	50	50	107
Product code suffix		-EL	-AS	-3
Available for		PO series upon request	ALTH series upon request	upon request

