

LEZ-VE series

Pressed steel castors with stem, wheel with standard solid rubber tyres



50–205 kg

Bracket: LEZ series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- steel plug-in stem and central kingpin bolted and secured


Wheel: VE series

- tyre: standard solid rubber, hardness 80 Shore A, colour black
- rim: pressed steel, zinc-plated, blue-passivated, Cr6-free

Additional details:

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 195
- bearing types: page 84–85

3



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Stem Ø (D) [mm]	Stem length [mm]	Offset swivel castor [mm]
LEZ-VE 80R	LEZ-VE 80R-FI	80	25	50	roller bearing	102	20	50	38
LEZ-VE 100R	LEZ-VE 100R-FI	100	30	70	roller bearing	125	20	50	36
LEZ-VE 125R	LEZ-VE 125R-FI	125	37.5	100	roller bearing	150	20	50	38
LEZ-VE 150R-22	LEZ-VE 150R-22-FI	150	40	135	roller bearing	190	22	60	54
LEZ-VE 150R-27	LEZ-VE 150R-27-FI	150	40	135	roller bearing	190	27	60	54
LEZ-VE 160R-22	LEZ-VE 160R-22-FI	160	40	135	roller bearing	195	22	60	54
LEZ-VE 160R-27	LEZ-VE 160R-27-FI	160	40	135	roller bearing	195	27	60	54
LEZ-VE 180R-22	LEZ-VE 180R-22-FI	180	50	170	roller bearing	215	22	60	54
LEZ-VE 180R-27	LEZ-VE 180R-27-FI	180	50	170	roller bearing	215	27	60	54
LEZ-VE 200R-22	LEZ-VE 200R-22-FI	200	50	205	roller bearing	235	22	60	54
LEZ-VE 200R-27	LEZ-VE 200R-27-FI	200	50	205	roller bearing	235	27	60	54

Versions / options



	with non-marking grey tyre	electrically conductive version, black tyre	with steel foot guard	with thread guard, pressed steel, zinc-plated
Technical description page	52	50	116	116
Product code suffix	-SG	-EL	-FS	-FA
Available for	all	all	upon request	upon request