

LHD-SE, BOD-SE, LHD-ALEV, BOD-ALEV series

Pressed steel twin wheel castors, heavy-duty brackets, with top plate, wheel with "Blickle EasyRoll" elastic solid rubber tyre



360–500 kg

Bracket: LHD/BOD series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free (fixed bracket: solid welded steel construction)
- heavy fork and top plate

Swivel bracket:

- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

Wheel: ALEV/SE series


- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: ALEV series: die-cast aluminium series SE: high-quality nylon 6, impact resistant, black

Additional details:

- bracket series: page 93
- wheel series: page 221, 228
- bearing types: page 84–85



3



| Swivel castors | Fixed castors | Wheel Ø [mm] | Wheel width [mm] | Load capacity [kg] | Bearing type | Total height [mm] | Plate size [mm] | Bolt hole spacing [mm] | Bolt hole Ø [mm] | Offset swivel castor [mm] |
|----------------------|----------------------|-----------------|---------------------|-----------------------|--------------|----------------------|--------------------|---------------------------|---------------------|------------------------------|
| LHD-SE 80K | BOD-SE 80K | 80 | 2 x 45 | 360 | ball bearing | 115 | 140 x 110 | 105 x 75–80 | 11 | 45 |
| LHD-ALEV 100K | BOD-ALEV 100K | 100 | 2 x 40 | 400 | ball bearing | 145 | 140 x 110 | 105 x 75–80 | 11 | 45 |
| LHD-ALEV 125K | BOD-ALEV 125K | 125 | 2 x 40 | 500 | ball bearing | 170 | 140 x 110 | 105 x 75–80 | 11 | 50 |

Fixed castors: long side of plate parallel to the wheel axle

Versions / options



| | with non-marking grey tyre | antistatic version, non-marking, grey tyre | electrically conductive version, black tyre |
|----------------------------|----------------------------|--|---|
| Technical description page | 52 | 53 | 50 |
| Product code suffix | -SG | -SG-AS | -EL |
| Available for | wheel Ø 100–125 mm | wheel Ø 100–125 mm | wheel Ø 100–125 mm |