

LKDG-PATH series

**Blickle MOVE twin synthetic castors
with bolt hole, colour silver grey,
wheel with thermoplastic polyurethane tread**

 100–125 kg

 -20 °C to +60 °C



Bracket: LKDG series

- high-quality nylon 6, impact resistant
- two grooved ball bearings in the swivel head sealed on both sides
- bolt hole
- colour silver grey RAL 7001
- modern, appealing design

Wheel: PATH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey RAL 7001


Other features:

- the load capacity reduces at ambient temperatures above +30 °C

Additional details:

- bracket series: page 89
- brakes: page 112–113
- wheel series: page 61
- bearing types: page 84–85

 **BLICKLE**
DESIGN LINE



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Total castor width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKDG-PATH 100K	LKDG-PATH 100K-FI	100	2 x 18	80	100	ball bearing	103	42	13	31
LKDG-PATH 100K-11	LKDG-PATH 100K-11-FI	100	2 x 18	80	100	ball bearing	103	42	11	31
LKDG-PATH 100K-9	LKDG-PATH 100K-9-FI	100	2 x 18	80	100	ball bearing	103	42	9	31
LKDG-PATH 125K	LKDG-PATH 125K-FI	125	2 x 20	80	125	ball bearing	130	42	13	40
LKDG-PATH 125K-11	LKDG-PATH 125K-11-FI	125	2 x 20	80	125	ball bearing	130	42	11	40

For corrosion-resistant versions of twin synthetic castors, see page 178

Swivel castor with "stop-fix" brake with easy release kick lever as standard

Versions / options *



	electrically conductive version, non-marking	with combined wheel brake and directional lock (1 x 360°)	castor with special mounting height 121 / 135 mm	with threaded pin M10 x 20 M12 x 20	wheel Ø 150 mm	with top plate fitting	in special colour
Technical description page	50	115		104		106	
Product code suffix	-ELS	-RIFI	LKDGH-...	-GS10 / -GS12		-P25 / -P26	
Available for	all	wheel Ø 125 mm	wheel Ø 100 / 125 mm	all with bolt hole Ø 13 mm	upon request	upon request**	upon request

* Other versions / options: expander fitting for all castors with bolt hole Ø 11 mm upon request (with exception of LKDGH version), total height +5 mm, see page 180

** Increases total height of castors by 8 mm