

## L-PATH, B-PATH series

**Pressed steel castors, medium-duty version, with top plate, wheel with thermoplastic polyurethane tread**



150–400 kg

**Bracket:** L/B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 150 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** PATH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey

**Additional details:**

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 258
- bearing types: page 84–85



**5**

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-PATH 80G	B-PATH 80G	L-PATH 80G-FI	80	32	150	plain bore	102	100 x 85	80 x 60	9	38
L-PATH 80KF	B-PATH 80KF	L-PATH 80KF-FI	80	32	150	ball bearing (C)	102	100 x 85	80 x 60	9	38
L-PATH 100G	B-PATH 100G	L-PATH 100G-FI	100	32	200	plain bore	125	100 x 85	80 x 60	9	36
L-PATH 100KF	B-PATH 100KF	L-PATH 100KF-FI	100	32	200	ball bearing (C)	125	100 x 85	80 x 60	9	36
L-PATH 125G	B-PATH 125G	L-PATH 125G-FI	125	32	250	plain bore	150	100 x 85	80 x 60	9	38
L-PATH 125KF	B-PATH 125KF	L-PATH 125KF-FI	125	32	250	ball bearing (C)	150	100 x 85	80 x 60	9	38
L-PATH 160G	B-PATH 160G	L-PATH 160G-FI	160	40	400	plain bore	195	140 x 110	105 x 75–80	11	60
L-PATH 160R	B-PATH 160R	L-PATH 160R-FI	160	40	400	roller bearing	195	140 x 110	105 x 75–80	11	60
L-PATH 160KA	B-PATH 160KA	L-PATH 160KA-FI	160	40	400	ball bearing (C)	195	140 x 110	105 x 75–80	11	60
L-PATH 200G	B-PATH 200G	L-PATH 200G-FI	200	40	400	plain bore	235	140 x 110	105 x 75–80	11	65
L-PATH 200R	B-PATH 200R	L-PATH 200R-FI	200	40	400	roller bearing	235	140 x 110	105 x 75–80	11	65
L-PATH 200KA	B-PATH 200KA	L-PATH 200KA-FI	200	40	400	ball bearing (C)	235	140 x 110	105 x 75–80	11	65

**Versions / options \***



	ball bearing version KF	electrically conductive version, non-marking grey	with "stop-top" brake	with "central-stop" central brake system	directional lock (separate) 1 x 360°	with steel foot guard
Technical description page		50	112	113	115	116
<b>Product code suffix</b>		<b>-ELS</b>	<b>-ST</b>	<b>-CS11</b>	<b>RI-03.01 / RI-05.03</b>	<b>-FS</b>
Available for		all ball bearing versions**	all	wheel Ø 160–200 mm	RI-03.01: Ø 100–125 RI-05.03: Ø 160–200 ***	wheel Ø 100–200 mm

\* Other versions / options: wheel with additional ball bearing seals (-KAD or -KFD), available upon request (see page 85 for technical information)

\*\* Wheel load capacity of electrically conductive version reduced by 35%

\*\*\* Only for swivel castors without brake or swivel castor with "stop-top" and "central-stop" brake upon request