

## LE-VE, B-VE series

### Pressed steel castors with top plate, wheel with standard solid rubber tyre



50–205 kg

**Bracket:** LE/B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**

- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process


**Wheel:** VE series

- tyre: standard solid rubber, hardness 80 Shore A, colour black
- rim: pressed steel, zinc-plated, blue-passivated, Cr6-free

**Additional details:**

- bracket series: page 90
- brakes: page 112–113
- wheel series: page 195
- bearing types: page 84–85

3



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LE-VE 80R	B-VE 80R	LE-VE 80R-FI	80	25	50	roller bearing	102	100 x 85	80 x 60	9	38
LE-VE 100R	B-VE 100R	LE-VE 100R-FI	100	30	70	roller bearing	125	100 x 85	80 x 60	9	36
LE-VE 125R	B-VE 125R	LE-VE 125R-FI	125	37.5	100	roller bearing	150	100 x 85	80 x 60	9	38
LE-VE 150R	B-VE 150R	LE-VE 150R-FI	150	40	135	roller bearing	190	140 x 110	105 x 75–80	11	54
LE-VE 160R	B-VE 160R	LE-VE 160R-FI	160	40	135	roller bearing	195	140 x 110	105 x 75–80	11	54
LE-VE 180R	B-VE 180R	LE-VE 180R-FI	180	50	170	roller bearing	215	140 x 110	105 x 75–80	11	54
LE-VE 200R	B-VE 200R	LE-VE 200R-FI	200	50	205	roller bearing	235	140 x 110	105 x 75–80	11	54

### Versions / options



	with non-marking grey tyre	electrically conductive version, black tyre	with thread guard, pressed steel, zinc-plated	with "stop-top" brake	with "central-stop" central brake system	directional lock (separate) 1 x 360°	with steel foot guard
Technical description page	52	50	116	112	113	115	116
<b>Product code suffix</b>	<b>-SG</b>	<b>-EL</b>	<b>-FA</b>	<b>-ST</b>	<b>-CS11</b>	<b>RI-03.01 / RI-03.03</b>	<b>-FS</b>
Available for	all	all	all	wheel Ø 150–200 mm	wheel Ø 160+200 mm	RI-03.01: Ø 100–125 RI-03.03: Ø 150–200 *	from wheel Ø 100 mm upon request

\* Only for swivel castors without brake or swivel castor with "stop-top" and "central-stop" brake upon request