

## LER-PPN series

### Pressed steel castors with bolt hole, with polypropylene wheel, natural white



80–300 kg

**Bracket:** LER series


- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** PPN series

- high-quality polypropylene, impact resistant, hardness 60 Shore D, colour natural white

**Additional details:**

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 332
- bearing types: page 84–85



6

Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LER-PPN 60G		60	29	80	plain bore	80	70	13	35
LER-PPN 80G	LER-PPN 80G-FI	80	32	120	plain bore	102	70	13	38
LER-PPN 80R	LER-PPN 80R-FI	80	32	120	roller bearing	102	70	13	38
LER-PPN 100G	LER-PPN 100G-FI	100	37	150	plain bore	125	70	13	36
LER-PPN 100R	LER-PPN 100R-FI	100	37	150	roller bearing	125	70	13	36
LER-PPN 125G	LER-PPN 125G-FI	125	40	150	plain bore	150	70	13	38
LER-PPN 125R	LER-PPN 125R-FI	125	40	150	roller bearing	150	70	13	38
LER-PPN 150G	LER-PPN 150G-FI	150	50	300	plain bore	190	88	13	54
LER-PPN 150R	LER-PPN 150R-FI	150	50	300	roller bearing	190	88	13	54
LER-PPN 200G	LER-PPN 200G-FI	200	50	300	plain bore	235	88	13	54
LER-PPN 200R	LER-PPN 200R-FI	200	50	300	roller bearing	235	88	13	54

### Versions / options



	electrically conductive version, colour black	with thread guard, pressed steel, zinc-plated	with steel foot guard	truck lock
Technical description page	434	116	116	114
<b>Product code suffix</b>	<b>PP...-EL series</b>	<b>-FA</b>	<b>-FS</b>	<b>FF 100-1 / FF 125-1</b>
Available for	see page 338	wheel Ø 80–200 mm	wheel Ø 100–200 mm upon request	wheel Ø 100+125 mm