

LER-PATH series

Pressed steel castors with bolt hole, wheel with thermoplastic polyurethane tread



150–300 kg

Bracket: LER series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process


Wheel: PATH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey

Additional details:

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 258
- bearing types: page 84–85

5



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LER-PATH 80G	LER-PATH 80G-FI	80	32	150	plain bore	102	70	13	38
LER-PATH 80KF	LER-PATH 80KF-FI	80	32	150	ball bearing (C)	102	70	13	38
LER-PATH 100G	LER-PATH 100G-FI	100	32	150	plain bore	125	70	13	36
LER-PATH 100KF	LER-PATH 100KF-FI	100	32	150	ball bearing (C)	125	70	13	36
LER-PATH 125G	LER-PATH 125G-FI	125	32	150	plain bore	150	70	13	38
LER-PATH 125KF	LER-PATH 125KF-FI	125	32	150	ball bearing (C)	150	70	13	38
LER-PATH 160G	LER-PATH 160G-FI	160	40	300	plain bore	195	88	13	54
LER-PATH 160R	LER-PATH 160R-FI	160	40	300	roller bearing	195	88	13	54
LER-PATH 160KA	LER-PATH 160KA-FI	160	40	300	ball bearing (C)	195	88	13	54
LER-PATH 200G	LER-PATH 200G-FI	200	40	300	plain bore	235	88	13	54
LER-PATH 200R	LER-PATH 200R-FI	200	40	300	roller bearing	235	88	13	54
LER-PATH 200KA	LER-PATH 200KA-FI	200	40	300	ball bearing (C)	235	88	13	54

For stainless steel versions, see page 408

Versions / options



	plain bore version	electrically conductive version, non-marking grey	small thread guard with additional ball bearing seal	large thread guard with additional ball bearing seals	truck lock
Technical description page		50	85	85	114
Product code suffix		-ELS	-KAD	-KFD	FF 100-1 / FF 125-1
Available for		all ball bearing versions*	upon request	upon request	wheel Ø 100+125 mm

* Wheel load capacity of electrically conductive version reduced by 35%