

LI-VKHT series

Heat-resistant pressed steel castors with top plate, with heat-resistant Blickle TempLine® Special wheel with solid rubber tyres



100 kg

-30 °C to +260 °C

Bracket: LI series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- smooth rolling characteristic and low wear, increased service life
- swivel head play is set specifically for high-temperature applications
- highly heat-resistant grease


Wheel: VKHT series

- tyre: highly heat-resistant solid rubber, hardness 85 Shore A, colour black
- rim: highly heat-resistant nylon 6, impact resistant, colour black

Additional details:

- bracket series: page 97
- brakes: page 112–113
- wheel series: page 445
- bearing types: page 84–85

Blickle TempLine® Special



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LI-VKHT 100G	LI-VKHT 100G-FI	100	30	100	plain bore	125	100 x 85	80 x 60	9	36

Versions / options



	with bolt hole, Ø 13 mm	with bolt hole, Ø 13 mm and "stop-fix" brake
Technical description page	97	112
Product code suffix	LIR-VKHT 100G	LIR-VKHT 100G-FI
Available for		