

GEVA series

**Heavy-duty hub fitting wheels
with elastic solid rubber tyres,
with cast iron wheel centre**



630–4,540 kg

Tread and tyre hardness

65 Shore A

Smooth operation / floor preservation

very good

Rolling resistance

very good

Wear resistance

satisfactory

Tyre:

- high-quality elastic solid rubber in smooth rolling quality, steel-wire reinforced, hardness 65 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- colour black

Wheel centre:

- rugged grey cast iron
- centre piece with a central hole and fitting holes
- fitting holes with domed anchor recesses
- lacquered, colour anthracite

Other features:

- fitted using domed anchor nuts and bolts in accordance with DIN 74361
- chemical resistance to many aggressive substances, except oils
- operating temperature: -30 °C to +80 °C, temporarily up to +100 °C, reduced load capacity over +60 °C

Additional details:

- wheel series: page 77
- tread: page 53
- bearing types: page 84–85
- chemical resistance: page 51

Wheels	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity at 4 km/h [kg]	Load capacity at 10 km/h [kg]	Load capacity at 16 km/h [kg]	Number of fitting holes	Fitting hole Ø (d2) [mm]	Central hole Ø (d) [mm]	PCD (d1) [mm]
GEVA 250/4	250	60	630	420	320	4	16.5	60	100
GEVA 252/4	250	80	810	540	410	4	16.5	60	100
GEVA 300/4	300	75	900	600	450	4	16.5	60	100
GEVA 300/5	300	75	900	600	450	5	16.5	67	112
GEVA 302/4	300	90	1,080	720	540	4	16.5	60	100
GEVA 302/5	300	90	1,080	720	540	5	16.5	67	112
GEVA 360/4	360	60	900	600	450	4	16.5	60	100
GEVA 360/5	360	60	900	600	450	5	16.5	67	112
GEVA 400/4	400	65	1,080	720	540	4	16.5	60	100
GEVA 400/5-67	400	65	1,080	720	540	5	16.5	67	112
GEVA 400/5-82	400	65	1,080	720	540	5	16.5	82	130
GEVA 402/4	400	75	1,200	800	600	4	16.5	60	100
GEVA 402/5-67	400	75	1,200	800	600	5	16.5	67	112
GEVA 402/5-82	400	75	1,200	800	600	5	16.5	82	130
GEVA 405/5	405	130	1,800	1,200	900	5	18.5	110	145
GEVA 405/6	405	130	1,800	1,200	900	6	21.5	160	205
GEVA 415/6	415	90	1,380	920	690	6	21.5	160	205
GEVA 500/6	500	85	1,560	1,050	780	6	21.5	160	205
GEVA 520/6	520	100	1,830	1,225	920	6	21.5	160	205
GEVA 620/6	620	200	4,540	3,105	2,835	6	21.5	160	205

Other dimensions available upon request

Versions / options



with pressed-on steel band in drive quality

Technical description page

Product code suffix **-STA**

Available for upon request

