

## LRA-VSTH, LKRA-VSTH series

**Light duty castors with bolt hole,  
wheel with Blickle Extrathane®  
polyurethane tread**



100–150 kg

**Bracket:** LRA/LKRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process


**Wheel:** VSTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown, non-marking, non-staining
- wheel centre: steel

**Additional details:**

- bracket series: page 86
- brakes: page 112–113
- wheel series: page 66
- bearing types: page 84–85

1



Swivel castors	Swivel castors with "Radstop" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LRA-VSTH 35K	LRA-VSTH 35K-RA	35	27	100	ball bearing	50	43	11	15
LKRA-VSTH 50K	LKRA-VSTH 50K-RA	50	33	150	ball bearing	70	57	13	29

For additional castors with a high load capacity and low total height, see the "Compact castors" section

### Versions / options



	with threaded pin M10 x 30	with threaded pin M12 x 30	buffers
Technical description page	104	104	116
Product code suffix	-GS10	-GS12	AG / ARG series
Available for	LRA-VSTH 35K*	LKRA-VSTH 50K	see page 148

\* Load capacity reduced by 20%