

GTH series, wheel Ø 250–1,000 mm

Heavy-duty wheels
with **Blickle Extrathane®** polyurethane tread,
with **cast iron wheel centre**



1,250–30,000 kg

Tread and tyre hardness
 92 Shore A

Smooth operation / floor preservation
 good

Rolling resistance
 very good

Wear resistance
 excellent



- Tread:**
- high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A
 - low rolling resistance
 - high abrasion resistance
 - high cut and tear propagation resistance
 - colour light brown, non-marking, non-staining
 - excellent chemical connection with the wheel centre

- Wheel centre:**
- rugged grey cast iron
 - with grease nipple
 - lacquered, colour silver

- Other features:**
- high chemical resistance to many aggressive substances
 - operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C

- Additional details:**
- wheel series: page 66
 - tread: page 55
 - bearing types: page 84–85
 - chemical resistance: page 51

Wheels	Wheel Ø	Wheel width	Load capacity at 4 km/h	Load capacity at 10 km/h	Bearing type	Axle bore Ø	Hub length
	(D) [mm]	(T2) [mm]	[kg]	[kg]		(d) [mm]	(T1) [mm]
GTH 251/25K	250	50	1,250	620	ball bearing	25	60
GTH 251/30K	250	50	1,250	620	ball bearing	30	60
GTH 250/25K	250	60	1,500	750	ball bearing	25	70
GTH 250/30K	250	60	1,500	750	ball bearing	30	70
GTH 250/30K-01	250	60	1,750	870	ball bearing	30	70
GTH 250/35K	250	60	1,500	750	ball bearing	35	70
GTH 252/25K	250	80	1,800	900	ball bearing	25	90
GTH 252/30K	250	80	2,200	1,100	ball bearing	30	90
GTH 254/40K	250	130	3,150	1,550	ball bearing	40	140
GTH 301/25K	300	45	1,300	650	ball bearing	25	60
GTH 300/30K	300	60	1,800	900	ball bearing	30	70
GTH 302/30K	300	80	2,400	1,200	ball bearing	30	90
GTH 302/35K	300	80	2,400	1,200	ball bearing	35	90
GTH 304/35K	300	100	3,000	1,500	ball bearing	35	120
GTH 360/40K	360	75	2,500	1,250	ball bearing	40	90
GTH 362/40K	360	80	3,000	1,500	ball bearing	40	90
GTH 363/40K	360	100	3,600	1,800	ball bearing	40	100
GTH 364/40K	360	120	3,800	1,900	ball bearing	40	120
GTH 400/35K	400	60	2,400	1,200	ball bearing	35	75
GTH 402/40K	400	80	3,000	1,500	ball bearing	40	90
GTH 404/40K	400	100	3,800	1,900	ball bearing	40	120
GTH 406/50K	400	125	5,000	2,500	ball bearing	50	125
GTH 500/50K	500	100	5,000	2,500	ball bearing	50	100
GTH 504/60K	500	150	7,500	3,750	ball bearing	60	150
GTH 506/80K	500	200	10,000	5,000	ball bearing	80	200
GTH 602/80K	600	150	9,000	4,500	ball bearing	80	150
GTH 604/80K	600	200	12,000	6,000	ball bearing	80	200
GTH 750/120K	750	200	15,000	7,500	ball bearing	120	200
GTH 1000/160PR	1,000	300	30,000	15,000	spherical roller bearing	160	330

Other dimensions available upon request

Versions / options



	antistatic version, non-marking grey	drive wheels with hub keyway	other shore hardnesses and special colours
Technical description page	50	75	
Product code suffix	-AS	GTHN series	
Available for	upon request	see page 541–542	upon request

