

VWPP series

Wheels with “Blickle Soft” soft rubber tyres, with synthetic rim



50–200 kg

Tread and tyre hardness

50 Shore A

Smooth operation / floor preservation

excellent

Rolling resistance

good

Wear resistance

satisfactory



3

- Tyre:**
- soft rubber “Blickle Soft”, highly elastic, round profile, hardness 50 Shore A
 - maximum operational comfort
 - excellent floor preservation, particularly quiet operation
 - colour black

- Rim:**
- high-quality polypropylene, impact resistant
 - colour black

- Other features:**
- high chemical resistance to many aggressive substances, except oils
 - operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
 - wheel Ø 260 mm with additional hard rubber core
 - puncture-proof alternatives for pneumatic tyres

Additional details:

- wheel series: page 62
- tread: page 52
- bearing types: page 84–85
- chemical resistance: page 51

Wheels	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Load capacity [kg]	Bearing type	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
VWPP 125/12G	125	37.5	50	plain bore	12	45
VWPP 125/12R	125	37.5	50	roller bearing	12	45
VWPP 160/20G	160	40	70	plain bore	20	60
VWPP 160/20R	160	40	70	roller bearing	20	60
VWPP 200/20G	200	50	100	plain bore	20	60
VWPP 200/20R	200	50	100	roller bearing	20	60
VWPP 250/25G	250	60	160	plain bore	25	65
VWPP 250/25R	250	60	160	roller bearing	25	65
VWPP 260/20G	260	85	200	plain bore	20	75
VWPP 260/20R	260	85	200	roller bearing	20	75
VWPP 260/20K	260	85	200	ball bearing	20	75

Versions / options



image	with non-marking grey tyre	with stainless steel roller bearing in the wheel hub
VWPP 260/20K		
Technical description page	52	84
Product code suffix	-SG	-XR
Available for	wheel Ø 125–200 mm, others upon request	upon request

