

## HRLK...-HN series

### Levelling castors with swiveling operating and release lever, with top plate

180–250 kg



**Bracket:** HRLK...-HN series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- steel truck lock with rubber pad
- height adjustment with swiveling operating and release lever

**Wheel:**

- PO series**
  - high-quality nylon 6, impact resistant, hardness 70 Shore D, colour natural white
- SPO series**
  - high-quality nylon 6, impact resistant, hardness 70 Shore D, extremely robust heavy-duty version, colour natural white
- ALTH series**
  - tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown
  - wheel centre: die-cast aluminium

**Additional details:**

- bracket series: page 99
- wheel series: page 69, 65
- bearing types: page 84–85

Swivel castors	Wheel Ø (D) [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height (H) [mm]	Total height max. (h) [mm]	Stroke (T4) [mm]	Floor clearance foot max. (T3) [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
<b>PO series</b>												
HRLK-PO 82G-HN	80	37	230	plain bore	117	121	4	12	100 x 85	80 x 60	9	56
<b>SPO series</b>												
HRLK-SPO 80G-HN	80	37	250	plain bore	117	121	4	12	100 x 85	80 x 60	9	56
<b>ALTH series</b>												
HRLK-ALTH 80K-HN	80	30	180	ball bearing	117	121	4	12	100 x 85	80 x 60	9	56

#### Versions / options



	image ALTH series	electrically-conductive version, wheel non-marking grey	antistatic version, non-marking grey	with top plate 140x110/105x75–80 mm
Technical description page	65	50	50	107
<b>Product code suffix</b>		<b>-EL</b>	<b>-AS</b>	<b>-3</b>
Available for		PO, SPO series upon request	ALTH series upon request	upon request

