

LRA-PATH, BRA-PATH, LKRA-PATH, BKRA-PATH series

Light duty castors with bolt hole,
wheel with thermoplastic
polyurethane tread

75–120 kg




- Bracket:** LRA/BRA, LKRA/BKRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- Swivel bracket:**
- double ball bearing in the swivel head
 - strong central kingpin
 - minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
 - synthetic "stop-fix" brake lever for series LRA, steel brake lever for series LKRA

- Wheel:** PATH series
- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
 - wheel centre: high-quality nylon 6, impact resistant, colour silver grey

- Additional details:**
- bracket series: page 86
 - brakes: page 112–113
 - wheel series: page 136
 - bearing types: page 84–85

1



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LRA-PATH 50G	BRA-PATH 50G	LRA-PATH 50G-FI *	50	19	75	plain bore	69	43	11	23
LRA-PATH 50KF	BRA-PATH 50KF	LRA-PATH 50KF-FI *	50	19	75	ball bearing (C)	69	43	11	23
LRA-PATH 75G	BRA-PATH 75G	LRA-PATH 75G-FI *	75	25	75	plain bore	98	43	11	29
LRA-PATH 75KF	BRA-PATH 75KF	LRA-PATH 75KF-FI *	75	25	75	ball bearing (C)	98	43	11	29
LKRA-PATH 80G	BKRA-PATH 80G	LKRA-PATH 80G-FI	80	32	120	plain bore	108	57	13	40
LKRA-PATH 80G-11		LKRA-PATH 80G-11-FI	80	32	120	plain bore	108	57	11	40
LKRA-PATH 80KF	BKRA-PATH 80KF	LKRA-PATH 80KF-FI	80	32	120	ball bearing (C)	108	57	13	40
LKRA-PATH 80KF-11		LKRA-PATH 80KF-11-FI	80	32	120	ball bearing (C)	108	57	11	40
LKRA-PATH 101G	BKRA-PATH 101G	LKRA-PATH 101G-FI	100	32	120	plain bore	133	57	13	40
LKRA-PATH 101G-11		LKRA-PATH 101G-11-FI	100	32	120	plain bore	133	57	11	40
LKRA-PATH 101KF	BKRA-PATH 101KF	LKRA-PATH 101KF-FI	100	32	120	ball bearing (C)	133	57	13	40
LKRA-PATH 101KF-11		LKRA-PATH 101KF-11-FI	100	32	120	ball bearing (C)	133	57	11	40
LKRA-PATH 126G	BKRA-PATH 126G	LKRA-PATH 126G-FI	125	32	120	plain bore	158	57	13	40
LKRA-PATH 126G-11		LKRA-PATH 126G-11-FI	125	32	120	plain bore	158	57	11	40
LKRA-PATH 126KF	BKRA-PATH 126KF	LKRA-PATH 126KF-FI	125	32	120	ball bearing (C)	158	57	13	40
LKRA-PATH 126KF-11		LKRA-PATH 126KF-11-FI	125	32	120	ball bearing (C)	158	57	11	40

* Synthetic brake lever, see image below

For stainless steel versions, see page 394

Versions / options**



	plain bore version	with synthetic brake lever	electrically conductive version, non-marking grey	with threaded pin M10 x 30 M12 x 30	with plug-in pin Ø 11 x 30.5	with synthetic expander fitting	with metal expander fitting
Technical description page			50	104	105	105	105
Product code suffix			-ELS	-GS10 / -GS12	-ES	see page 148	see page 148
Available for		series LRA...-FI as standard	all ball bearing versions***	-GS10: series LRA -GS12: series LKRA	series LRA swivel castors****	swivel castors with bolt hole Ø 11 mm (except ELS)	swivel castors with bolt hole Ø 11 mm

** Other versions / options: 1. bracket in special colours (electrostatic powder coating), available upon request 2. buffers AG / ARG series see page 148 (page 116 for technical information)

*** Wheel load capacity of electrically conductive version reduced by 35%

**** Synthetic castor socket for round tubes see page 148