

## LIX-VKHT series

**Heat-resistant stainless steel castors with top plate, with heat-resistant Blickle TempLine® Special wheel with solid rubber tyres**

100 kg

-30 °C to +260 °C

**Bracket:** LIX series

- high-quality chromium-nickel steel (1.4301/AISI 304), stainless steel, vibration-ground finishing
- double ball bearing in the swivel head
- strong central kingpin
- smooth rolling characteristic and low wear, increased service life
- swivel head play is set specifically for high-temperature applications
- grease-free as standard ("-OF")
- PTFE coated stainless steel axle tube
- all parts including axle material are corrosion-resistant

**Wheel:** VKHT series


- tyre: highly heat-resistant solid rubber, hardness 85 Shore A, colour black
- rim: highly heat-resistant nylon 6, impact resistant, colour black

**Additional details:**

- bracket series: page 98
- brakes: page 112–113
- wheel series: page 445
- bearing types: page 84–85



Blickle TempLine® Special



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LIX-VKHT 100G-OF	LIX-VKHT 100G-FI-OF	100	30	100	plain bore	125	100 x 85	80 x 60	9	36

### Versions / options



	with bolt hole, Ø 13 mm	with bolt hole, Ø 13 mm and "stop-fix" brake	with highly heat-resistant grease -30 °C to +250 °C
Technical description page	98	112	
<b>Product code suffix</b>	<b>LIXR-VKHT 100G-OF</b>	<b>LIXR-VKHT 100G-FI-OF</b>	<b>remove -OF suffix</b>
Available for			upon request