

LKDGX-PATH series

Blickle MOVE twin synthetic castors, corrosion-resistant, with bolt hole, colour silver grey, wheel with thermoplastic polyurethane tread



100–125 kg

-20 °C to +60 °C

Bracket: LKDGX series

- high-quality nylon 6, impact resistant
- two corrosion-resistant grooved ball bearings in swivel head sealed on both sides
- bolt hole
- colour silver grey RAL 7001
- all parts including axle material are corrosion-resistant
- modern, appealing design

Wheel: PATH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey RAL 7001

Other features:


- the load capacity reduces at ambient temperatures above +30 °C

Additional details:

- bracket series: page 90
- brakes: page 112–113
- wheel series: page 61
- bearing types: page 84–85



2



| Swivel castors | Swivel castors with "stop-fix" brake | Wheel Ø [mm] | Wheel width [mm] | Total castor width [mm] | Load capacity [kg] | Bearing type | Total height [mm] | Plate Ø [mm] | Bolt hole Ø [mm] | Offset swivel castor [mm] |
|---------------------|--------------------------------------|-----------------|---------------------|----------------------------|-----------------------|--------------|----------------------|-----------------|---------------------|------------------------------|
| LKDGX-PATH 100XK | LKDGX-PATH 100XK-FI | 100 | 2 x 18 | 80 | 100 | ball bearing | 103 | 42 | 13 | 31 |
| LKDGX-PATH 100XK-11 | LKDGX-PATH 100XK-11-FI | 100 | 2 x 18 | 80 | 100 | ball bearing | 103 | 42 | 11 | 31 |
| LKDGX-PATH 100XK-9 | LKDGX-PATH 100XK-9-FI | 100 | 2 x 18 | 80 | 100 | ball bearing | 103 | 42 | 9 | 31 |
| LKDGX-PATH 125XK | LKDGX-PATH 125XK-FI | 125 | 2 x 20 | 80 | 125 | ball bearing | 130 | 42 | 13 | 40 |
| LKDGX-PATH 125XK-11 | LKDGX-PATH 125XK-11-FI | 125 | 2 x 20 | 80 | 125 | ball bearing | 130 | 42 | 11 | 40 |

Swivel castor with "stop-fix" brake with easy release kick lever as standard

Versions / options *



| | electrically conductive version, non-marking | with combined wheel brake and directional lock (1 x 360°) | castor with special mounting height 121 / 135 mm | with threaded pin made from stainless steel M10 x 20 M12 x 20 | wheel Ø 150 mm | with stainless steel top plate fitting | in special colour |
|----------------------------|--|---|--|---|----------------|--|-------------------|
| Technical description page | 50 | 115 | | 104 | | 106 | |
| Product code suffix | -ELS | -RIFI | LKDGXH-... | -GSX10 / -GSX12 | | -PX25 / -PX26 | |
| Available for | all | wheel Ø 125 mm | wheel Ø 100 / 125 mm | all with bolt hole Ø 13 mm | upon request | upon request | upon request |

* Other versions / options: expander fitting for all castors with bolt hole Ø 11 mm upon request (with exception of LKDGXH version), total height +5 mm, see page 180