

SETH series

Heavy-duty wheels
with **Blickle Extrathane®** polyurethane tread,
with **welded steel wheel centre**



500–1,350 kg

Tread and tyre hardness
 92 Shore A

Smooth operation / floor preservation
 good

Rolling resistance
 very good

Wear resistance
 excellent



5

- Tread:**
- high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A
 - low rolling resistance
 - high abrasion resistance
 - high cut and tear propagation resistance
 - colour light brown, non-marking, non-staining
 - excellent chemical connection with the wheel centre

- Wheel centre:**
- thick-walled pressed steel, triple welded
 - with welded tubular steel hub
 - resistant to dirt, impact and shocks
 - lacquered, colour silver

- Other features:**
- high chemical resistance to many aggressive substances
 - operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C

- Additional details:**
- wheel series: page 66
 - tread: page 55
 - bearing types: page 84–85
 - chemical resistance: page 51

Wheels	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity at 4 km/h [kg]	Load capacity at 10 km/h [kg]	Bearing type	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
SETH 125/20K	125	50	500	250	ball bearing	20	60
SETH 150/20K	150	50	650	320	ball bearing	20	60
SETH 150/25K	150	50	650	320	ball bearing	25	60
SETH 160/20K	160	50	700	350	ball bearing	20	60
SETH 160/25K	160	50	700	350	ball bearing	25	60
SETH 200/20K	200	50	1,000	500	ball bearing	20	60
SETH 200/25K	200	50	1,000	500	ball bearing	25	60
SETH 250/25K	250	60	1,350	670	ball bearing	25	70

Versions / options



with grease nipple other shore hardnesses
and special colours

Technical description page

Product code suffix **-NI**

Available for upon request upon request

