


Twin wheel compact castors

 210–250 kg



Bracket: LD series

- swivel bracket: zinc die-cast
- high-quality ball bearing in the swivel head
- zinc-plated steel threaded pin
- bracket series: page 99



Wheel: POEV series

- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: high-quality nylon 6, impact resistant, colour black
- detailed description: page 63, 212



Wheel: VSTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown, non-marking, non-staining
- wheel centre: steel
- detailed description: page 66, 286



Wheel: POA series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black
- detailed description: page 61, 143



Wheel: PO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour natural white
- detailed description: page 69, 343

Swivel castors	Wheel Ø [mm]	Wheel width [mm]	Total castor width [mm]	Load capacity at 3 km/h [kg]	Bearing type	Total height [mm]	Threaded pin [mm]	Offset swivel castor [mm]
LD series								
LD-POA 52G	50	2 x 29	95	210	plain bore	56	M16 x 20	39
LD-VSTH 50K	50	2 x 33	100	250	ball bearing	56	M16 x 20	39
LD-PO 60G	60	2 x 29	105	250	plain bore	65	M16 x 20	39
LD-POEV 60KF	60	2 x 34	105	240	ball bearing (CC)	65	M16 x 20	39
LD-VSTH 60K	60	2 x 35	105	250	ball bearing	65	M16 x 20	39