

PK series

Wheels with pneumatic tyres, with synthetic rim



75–250 kg

Tread and tyre hardness
 60 Shore A

Smooth operation / floor preservation
 excellent

Rolling resistance
 good

Wear resistance
 satisfactory

- Tyre:**
- pneumatic tyre, ribbed or zig-zag profile, hardness 60 Shore A
 - 2-ply rating, with inner tube
 - excellent floor preservation, particularly quiet operation
 - colour black

- operating temperature: -20 °C to +40 °C, reduced load capacity over +30 °C
- the wheel and tyre dimensions provided here apply to new tyres that are not bearing a load. Their width and diameter may change when they are in use.

- Rim:**
- high-quality polypropylene, impact resistant
 - colour black

- Additional details:**
- wheel series: page 64
 - tread: page 54
 - bearing types: page 84–85
 - chemical resistance: page 51

- Other features:**
- high chemical resistance to many aggressive substances, except oils

4

Wheels	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Tyre size	Ply rating	Load capacity at 4 km/h [kg]	Tyre pressure [bar / psi]	Bearing type	Axle bore Ø (d) [mm]	Hub length (T1) [mm]	Profile type
Wheels with ribbed profile										
PK 200/20-60G	200	50	200x50	2	75	2.5 / 36	plain bore	20	60	R01
PK 260/20-75G	260	85	3.00-4	2	150	2.0 / 30	plain bore	20	75	R01
PK 260/25-75G	260	85	3.00-4	2	150	2.0 / 30	plain bore	25	75	R01
PK 260/20-75R	260	85	3.00-4	2	150	2.0 / 30	roller bearing	20	75	R01
PK 260/25-75R	260	85	3.00-4	2	150	2.0 / 30	roller bearing	25	75	R01
PK 260/20-75K	260	85	3.00-4	2	150	2.0 / 30	ball bearing	20	75	R01
PK 300/20-75G	300	100	4.00-4	2	180	2.0 / 30	plain bore	20	75	R01
PK 300/25-75G	300	100	4.00-4	2	180	2.0 / 30	plain bore	25	75	R01
PK 300/20-75R	300	100	4.00-4	2	180	2.0 / 30	roller bearing	20	75	R01
PK 300/25-75R	300	100	4.00-4	2	180	2.0 / 30	roller bearing	25	75	R01
PK 300/20-75K	300	100	4.00-4	2	180	2.0 / 30	ball bearing	20	75	R01
PK 400/20-75G	400	100	4.00-8	2	250	2.0 / 30	plain bore	20	75	R01
PK 400/25-75G	400	100	4.00-8	2	250	2.0 / 30	plain bore	25	75	R01
PK 400/20-75R	400	100	4.00-8	2	250	2.0 / 30	roller bearing	20	75	R01
PK 400/25-75R	400	100	4.00-8	2	250	2.0 / 30	roller bearing	25	75	R01
Wheels with zig-zag profile										
PK 257/20-75G	260	85	3.00-4	2	150	2.0 / 30	plain bore	20	75	B04
PK 262/20-75G	260	85	3.00-4	2	150	2.0 / 30	plain bore	20	75	B02
PK 262/25-75G	260	85	3.00-4	2	150	2.0 / 30	plain bore	25	75	B02
PK 262/20-75R	260	85	3.00-4	2	150	2.0 / 30	roller bearing	20	75	B02
PK 262/25-75R	260	85	3.00-4	2	150	2.0 / 30	roller bearing	25	75	B02
PK 262/20-75K	260	85	3.00-4	2	150	2.0 / 30	ball bearing	20	75	B02
PK 302/20-75G	300	100	4.00-4	2	180	2.0 / 30	plain bore	20	75	B02
PK 302/25-75G	300	100	4.00-4	2	180	2.0 / 30	plain bore	25	75	B02
PK 302/20-75R	300	100	4.00-4	2	180	2.0 / 30	roller bearing	20	75	B02
PK 302/25-75R	300	100	4.00-4	2	180	2.0 / 30	roller bearing	25	75	B02
PK 302/20-75K	300	100	4.00-4	2	180	2.0 / 30	ball bearing	20	75	B02
PK 402/20-75G	400	100	4.00-8	2	250	2.0 / 30	plain bore	20	75	B07
PK 402/25-75G	400	100	4.00-8	2	250	2.0 / 30	plain bore	25	75	B07
PK 402/20-75R	400	100	4.00-8	2	250	2.0 / 30	roller bearing	20	75	B07
PK 402/25-75R	400	100	4.00-8	2	250	2.0 / 30	roller bearing	25	75	B07

Profile types: R = ribbed profile, B = zig-zag profile, see page 248 for image

Versions / options



rim colour red puncture-proof soft rubber wheels

Technical description page	62	
Product code suffix	-ROT	VWPP series
Available for	wheel Ø 260–400 mm	see page 202

