

## LKR-POTH series

**Pressed steel castors, heavy-duty design, with bolt hole, wheel with thermoplastic polyurethane tread**



200–350 kg

**Bracket:** LKR series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process


**Wheel:** POTH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour natural white

**Additional details:**

- bracket series: page 92
- brakes: page 112–113
- wheel series: page 263
- bearing types: page 84–85

5



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKR-POTH 75G	LKR-POTH 75G-FI	75	37	200	plain bore	108	88	13	40
LKR-POTH 75R	LKR-POTH 75R-FI	75	37	200	roller bearing	108	88	13	40
LKR-POTH 100G	LKR-POTH 100G-FI	100	35	300	plain bore	130	88	13	45
LKR-POTH 100R	LKR-POTH 100R-FI	100	35	300	roller bearing	130	88	13	45
LKR-POTH 100KA	LKR-POTH 100KA-FI	100	35	300	ball bearing (C)	130	88	13	45
LKR-POTH 125G	LKR-POTH 125G-FI	125	40	350	plain bore	155	88	13	48
LKR-POTH 125R	LKR-POTH 125R-FI	125	40	350	roller bearing	155	88	13	48
LKR-POTH 125KA	LKR-POTH 125KA-FI	125	40	350	ball bearing (C)	155	88	13	48

### Versions / options



	with thread guard, pressed steel, zinc-plated	small thread guard with additional ball bearing seal	truck lock
Technical description page	116	85	114
<b>Product code suffix</b>	<b>-FA</b>	<b>-KAD</b>	<b>FF 100-1 / FF 125-1</b>
Available for	wheel Ø 100–125 mm	upon request	wheel Ø 100+125 mm