

SE series

**Heavy-duty wheels with elastic solid rubber tyre
“Blickle EasyRoll”, with welded steel
wheel centre or nylon wheel centre**



200–1,150 kg

Tread and tyre hardness

65 Shore A

Smooth operation / floor preservation

very good

Rolling resistance

very good

Wear resistance

good



3

Tyre:

- high-quality elastic solid rubber “Blickle EasyRoll” in smooth rolling quality, hardness 65 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- colour black
- vulcanised onto the wheel centre or product code ...-Z: steel-wire reinforced and pressed-on

Wheel centre:

- thick-walled pressed steel, with tubular steel hub, triple welded
- resistant to dirt, impact and shocks
- lacquered, colour anthracite
- wheel Ø 80–125 mm made from high-quality nylon 6, impact resistant, colour black

Other features:

- chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +80 °C, temporarily up to +100 °C, reduced load capacity over +60 °C


Additional details:

- wheel series: page 63
- tread: page 53
- bearing types: page 84–85
- chemical resistance: page 51

Wheels	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity at 4 km/h [kg]	Load capacity at 10 km/h [kg]	Bearing type	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
SE 80/20K	80	45	200	–	ball bearing	20	45
SE 100/20K	100	45	270	–	ball bearing	20	45
SE 125/20K	125	53	320	180	ball bearing	20	60
SE 160/20K	160	50	450	250	ball bearing	20	60
SE 200/20K	200	50	600	350	ball bearing	20	60
SE 200/25K	200	50	600	350	ball bearing	25	60
SE 202/25K	200	80	850	500	ball bearing	25	90
SE 250/25K	250	60	850	500	ball bearing	25	70
SE 252/25K	250	80	1,000	600	ball bearing	25	90
SE 252/30K	250	80	1,000	600	ball bearing	30	90
SE 300/30K	300	75	1,000	650	ball bearing	30	85
SE 360/30K-Z	360	75	950	760	ball bearing	30	90
SE 400/35K-Z	400	65	900	720	ball bearing	35	75
SE 415/35K-Z	415	90	1,150	920	ball bearing	35	100

For other dimensions, see wheel series GEV on page 234

Versions / options



with non-marking grey tyre

with grease nipple

Technical description page

52

Product code suffix

-SG

-NI

Available for

wheel Ø 125–200 mm,
others upon request

wheel Ø 200–415 mm
upon request

