

## LDA-PATH series

### Twin wheel light duty castors with top plate, wheels with thermoplastic polyurethane tread



80–100 kg

**Bracket:** LDA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- pressed swivel head


**Wheel:** PATH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey

**Additional details:**

- bracket series: page 86
- brakes: page 112–113
- wheel series: page 136
- bearing types: page 84–85

1



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LDA-PATH 50G	LDA-PATH 50G-FI	50	2 x 19	80	plain bore	71	60 x 60	38 x 38 / 48 x 48	6.2	31
LDA-PATH 50KF	LDA-PATH 50KF-FI	50	2 x 19	80	ball bearing (C)	71	60 x 60	38 x 38 / 48 x 48	6.2	31
LDA-PATH 75G	LDA-PATH 75G-FI	75	2 x 25	100	plain bore	101	60 x 60	40 x 40 / 46 x 46	6.2	34
LDA-PATH 75KF	LDA-PATH 75KF-FI	75	2 x 25	100	ball bearing (C)	101	60 x 60	40 x 40 / 46 x 46	6.2	34

### Versions / options



	plain bore version	electrically conductive version, non-marking grey
Technical description page		50
Product code suffix		-ELS
Available for		all ball bearing versions*

\* Wheel load capacity of electrically conductive version reduced by 35%