

## LEXR-PO series

### Stainless steel castors with bolt hole, with nylon wheel

150–300 kg

**Bracket:** LEXR series


- high-quality chromium-nickel steel (1.4301/AISI 304), stainless steel, vibration-ground finishing
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- all parts including axle material are corrosion-resistant

**Wheel:** PO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour natural white

**Additional details:**

- bracket series: page 96
- brakes: page 112–113
- wheel series: page 69
- bearing types: page 84–85



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LEXR-PO 75G	LEXR-PO 75G-FI	75	32	150	plain bore	100	70	13	38
LEXR-PO 75XR	LEXR-PO 75XR-FI	75	32	150	roller bearing	100	70	13	38
LEXR-PO 80G	LEXR-PO 80G-FI	80	32	150	plain bore	102	70	13	38
LEXR-PO 80XR	LEXR-PO 80XR-FI	80	32	150	roller bearing	102	70	13	38
LEXR-PO 80KAD	LEXR-PO 80KAD-FI	80	32	150	ball bearing (C)	102	70	13	38
LEXR-PO 100G	LEXR-PO 100G-FI	100	37	150	plain bore	125	70	13	36
LEXR-PO 100XR	LEXR-PO 100XR-FI	100	37	150	roller bearing	125	70	13	36
LEXR-PO 100KAD	LEXR-PO 100KAD-FI	100	37	150	ball bearing (C)	125	70	13	36
LEXR-PO 125G	LEXR-PO 125G-FI	125	40	150	plain bore	150	70	13	38
LEXR-PO 125XR	LEXR-PO 125XR-FI	125	40	150	roller bearing	150	70	13	38
LEXR-PO 125KAD	LEXR-PO 125KAD-FI	125	40	150	ball bearing (C)	150	70	13	38
LEXR-PO 150G	LEXR-PO 150G-FI	150	50	300	plain bore	190	88	13	54
LEXR-PO 150XR	LEXR-PO 150XR-FI	150	50	300	roller bearing	190	88	13	54
LEXR-PO 160G	LEXR-PO 160G-FI	160	50	300	plain bore	195	88	13	54
LEXR-PO 160XR	LEXR-PO 160XR-FI	160	50	300	roller bearing	195	88	13	54
LEXR-PO 200G	LEXR-PO 200G-FI	200	50	300	plain bore	235	88	13	54
LEXR-PO 200XR	LEXR-PO 200XR-FI	200	50	300	roller bearing	235	88	13	54

8

#### Versions / options



	electrically conductive version, non-marking grey	with stainless steel ball bearing and small thread guard	with synthetic foot guard
Technical description page	50	85	116
<b>Product code suffix</b>	<b>-ELS</b>	<b>-XKA</b>	<b>-FP</b>
Available for	see series PO...-ELS (page 435)	upon request	wheel Ø 125 mm upon request