

## LE-PATH, B-PATH series

**Pressed steel castors with top plate,  
wheel with thermoplastic  
polyurethane tread**



150–300 kg

**Bracket:** LE/B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** PATH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey

**Additional details:**

- bracket series: page 90
- brakes: page 112–113
- wheel series: page 258
- bearing types: page 84–85



**5**

| Swivel castors | Fixed castors | Swivel castors with "stop-fix" brake | Wheel Ø<br>[mm] | Wheel width<br>[mm] | Load capacity<br>[kg] | Bearing type     | Total height<br>[mm] | Plate size<br>[mm] | Bolt hole spacing<br>[mm] | Bolt hole Ø<br>[mm] | Offset swivel castor<br>[mm] |
|----------------|---------------|--------------------------------------|-----------------|---------------------|-----------------------|------------------|----------------------|--------------------|---------------------------|---------------------|------------------------------|
| LE-PATH 80G    | B-PATH 80G    | LE-PATH 80G-FI                       | 80              | 32                  | 150                   | plain bore       | 102                  | 100 x 85           | 80 x 60                   | 9                   | 38                           |
| LE-PATH 80KF   | B-PATH 80KF   | LE-PATH 80KF-FI                      | 80              | 32                  | 150                   | ball bearing (C) | 102                  | 100 x 85           | 80 x 60                   | 9                   | 38                           |
| LE-PATH 100G   | B-PATH 100G   | LE-PATH 100G-FI                      | 100             | 32                  | 150                   | plain bore       | 125                  | 100 x 85           | 80 x 60                   | 9                   | 36                           |
| LE-PATH 100KF  | B-PATH 100KF  | LE-PATH 100KF-FI                     | 100             | 32                  | 150                   | ball bearing (C) | 125                  | 100 x 85           | 80 x 60                   | 9                   | 36                           |
| LE-PATH 125G   | B-PATH 125G   | LE-PATH 125G-FI                      | 125             | 32                  | 150                   | plain bore       | 150                  | 100 x 85           | 80 x 60                   | 9                   | 38                           |
| LE-PATH 125KF  | B-PATH 125KF  | LE-PATH 125KF-FI                     | 125             | 32                  | 150                   | ball bearing (C) | 150                  | 100 x 85           | 80 x 60                   | 9                   | 38                           |
| LE-PATH 160G   | B-PATH 160G   | LE-PATH 160G-FI                      | 160             | 40                  | 300                   | plain bore       | 195                  | 140 x 110          | 105 x 75–80               | 11                  | 54                           |
| LE-PATH 160R   | B-PATH 160R   | LE-PATH 160R-FI                      | 160             | 40                  | 300                   | roller bearing   | 195                  | 140 x 110          | 105 x 75–80               | 11                  | 54                           |
| LE-PATH 160KA  | B-PATH 160KA  | LE-PATH 160KA-FI                     | 160             | 40                  | 300                   | ball bearing (C) | 195                  | 140 x 110          | 105 x 75–80               | 11                  | 54                           |
| LE-PATH 200G   | B-PATH 200G   | LE-PATH 200G-FI                      | 200             | 40                  | 300                   | plain bore       | 235                  | 140 x 110          | 105 x 75–80               | 11                  | 54                           |
| LE-PATH 200R   | B-PATH 200R   | LE-PATH 200R-FI                      | 200             | 40                  | 300                   | roller bearing   | 235                  | 140 x 110          | 105 x 75–80               | 11                  | 54                           |
| LE-PATH 200KA  | B-PATH 200KA  | LE-PATH 200KA-FI                     | 200             | 40                  | 300                   | ball bearing (C) | 235                  | 140 x 110          | 105 x 75–80               | 11                  | 54                           |

For stainless steel versions, see page 407

### Versions / options



|                            | plain bore version | electrically conductive version, non-marking grey | with "stop-top" brake | directional lock (separate) 1 x 360°             | small thread guard with additional ball bearing seal | large thread guard with additional ball bearing seals |
|----------------------------|--------------------|---|-----------------------|--|--|---|
| Technical description page |                    | 50  | 112                   | 115  | 85   | 85  |
| <b>Product code suffix</b> |                    | <b>-ELS</b>                                       | <b>-ST</b>            | <b>RI-03.01 / RI-03.03</b>                       | <b>-KAD</b>  | <b>-KFD</b>   |
| Available for              |                    | all ball bearing versions*                        | wheel Ø 160–200 mm    | RI-03.01: Ø 100–125<br>RI-03.03: Ø 160–200<br>** | upon request   | upon request  |

\* Wheel load capacity of electrically conductive version reduced by 35%

\*\* Only for swivel castors without brake or swivel castor with "stop-top" brake upon request