

LIR-VEHI series

Heat-resistant pressed steel castors
with bolt hole, with heat-resistant
Blickle TempLine® Basic wheel with solid rubber tyres



 **Blickle**
TempLine® Basic


 65–90 kg

 -25 °C to +200 °C

- Bracket:** LIR series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
 - double ball bearing in the swivel head
 - strong central kingpin
 - smooth rolling characteristic and low wear, increased service life
 - swivel head play is set specifically for high-temperature applications
 - highly heat-resistant grease

- Wheel:** VEHI series
- tyre: highly heat-resistant solid rubber, hardness 80 Shore A, colour black
 - rim: pressed steel, zinc-plated, blue-passivated, Cr6-free

- Additional details:**
- bracket series: page 97
 - brakes: page 112–113
 - wheel series: page 442
 - bearing types: page 84–85



Swivel castors	Swivel castors with “stop-fix” brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LIR-VEHI 100R	LIR-VEHI 100R-FI	100	30	65	roller bearing	125	70	13	36
LIR-VEHI 125R	LIR-VEHI 125R-FI	125	37.5	90	roller bearing	150	70	13	38