

## LEXZ-PO series

### Stainless steel castors with stem, with nylon wheel

150–300 kg

**Bracket:** LEXZ series


- high-quality chromium-nickel steel (1.4301/AISI 304), stainless steel, vibration-ground finishing
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- stainless steel plug-in stem and central kingpin bolted and secured
- all parts including axle material are corrosion-resistant

**Wheel:** PO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour natural white

**Additional details:**

- bracket series: page 96
- brakes: page 112–113
- wheel series: page 69
- bearing types: page 84–85



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Stem Ø [mm]	Stem length [mm]	Offset swivel castor [mm]
LEXZ-PO 75G	LEXZ-PO 75G-FI	75	32	150	plain bore	100	20	50	38
LEXZ-PO 80G	LEXZ-PO 80G-FI	80	32	150	plain bore	102	20	50	38
LEXZ-PO 100G	LEXZ-PO 100G-FI	100	37	150	plain bore	125	20	50	36
LEXZ-PO 125G	LEXZ-PO 125G-FI	125	40	150	plain bore	150	20	50	38
LEXZ-PO 150G	LEXZ-PO 150G-FI	150	50	300	plain bore	190	27	60	54
LEXZ-PO 160G	LEXZ-PO 160G-FI	160	50	300	plain bore	195	27	60	54
LEXZ-PO 200G	LEXZ-PO 200G-FI	200	50	300	plain bore	235	27	60	54

8

### Versions / options



	electrically conductive version, non-marking grey	with synthetic foot guard
Technical description page	50	116
<b>Product code suffix</b>	<b>-ELS</b>	<b>-FP</b>
Available for	see series PO...-ELS (page 435)	wheel Ø 125 mm upon request