

VW series

Wheels with “Blickle Soft” soft rubber tyres,
with pressed steel rim

 50–200 kg

Tread and tyre hardness



50 Shore A

Smooth operation / floor preservation



excellent

Rolling resistance



good

Wear resistance



satisfactory



Tyre:

- soft rubber “Blickle Soft”, highly elastic, round profile, hardness 50 Shore A
- maximum operational comfort
- excellent floor preservation, particularly quiet operation
- colour black

Rim:

- pressed steel
- strong rim structure with tubular steel hub, bolted or pressed
- zinc-plated, blue-passivated, Cr6-free

Other features:

- chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +80 °C, reduced load capacity over +60 °C
- wheel Ø 260 mm with additional hard rubber core
- puncture-proof alternatives for pneumatic tyres

Additional details:

- wheel series: page 62
- tread: page 52
- bearing types: page 84–85
- chemical resistance: page 51

Wheels	Wheel Ø (D) [mm]	Tyre width (T2) [mm]	Load capacity [kg]	Bearing type	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
VW 125/15R	125	37.5	50	roller bearing	15	45
VW 162/20R	160	40	70	roller bearing	20	60
VW 202/20R	200	50	100	roller bearing	20	60
VW 252/25R	250	60	160	roller bearing	25	65
VW 260/20R *	260	85	200	roller bearing	20	75
VW 260/20K *	260	85	200	ball bearing	20	75

* Bolted version

Versions / options



image VW 260/20K

with non-marking
grey tyre

Technical description page

52

Product code suffix

-SG

Available for

wheel Ø 125–200 mm,
others upon request

