

LO-ALEV, BO-ALEV series

**Welded steel heavy-duty castors,
wheel with "Blickle EasyRoll" elastic solid rubber tyre**



300–650 kg

Bracket: LO/BO series

- solid welded steel construction, zinc-plated, blue-passivated, Cr6-free

Swivel bracket:

- double ball bearing in the swivel head
- **four specially-shaped, hardened bearing seats** for additional strength
- bolted and secured welded central kingpin, extremely strong
- swivel head seal with labyrinth design
- grease nipple

Wheel: ALEV series


- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: die-cast aluminium

Additional details:

- bracket series: page 93
- brakes: page 112–113
- wheel series: page 221
- bearing types: page 84–85



3



Swivel castors	Fixed castors	Swivel castor with "stop-top" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LO-ALEV 127K	BO-ALEV 127K	LO-ALEV 127K-ST	125	50	300	ball bearing	170	140 x 110	105 x 75–80	11	50
LO-ALEV 150K	BO-ALEV 150K	LO-ALEV 150K-ST	150	50	400	ball bearing	200	140 x 110	105 x 75–80	11	55
LO-ALEV 160K	BO-ALEV 160K	LO-ALEV 160K-ST	160	50	400	ball bearing	205	140 x 110	105 x 75–80	11	55
LO-ALEV 200K	BO-ALEV 200K	LO-ALEV 200K-ST	200	50	500	ball bearing	245	140 x 110	105 x 75–80	11	60
LO-ALEV 250K	BO-ALEV 250K	LO-ALEV 250K-ST	250	50	650	ball bearing	295	140 x 110	105 x 75–80	11	70

Versions / options



	with non-marking grey tyre	antistatic version, non-marking, grey tyre	electrically conductive version, black tyre	with directional lock 4 x 90°	with steel foot guard	truck lock
Technical description page	52	53	50	115	116	114
Product code suffix	-SG	-SG-AS	-EL	-RI4	-FS	FF 125 / 150 / 160 / 200
Available for	all	wheel Ø 160–250 mm	wheel Ø 160–250 mm	wheel Ø 125–200 mm	upon request	wheel Ø 125–200 mm