

## LWKX-TPA series

**Blickle WAVE synthetic castors, corrosion-resistant, with top plate, colour grey white, wheel with thermoplastic rubber tread**



100–110 kg

-20 °C to +60 °C

**Bracket:** LWKX series

- high-quality nylon 6, impact resistant
- moulded corrosion-resistant grooved ball bearing in the swivel head sealed on both sides
- with top plate fitting made of stainless steel
- colour grey white RAL 9002
- all parts including axle material are corrosion-resistant
- modern, appealing design

**Wheel:** TPA series

- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour grey white RAL 9002

**Other features:**


- the load capacity reduces at ambient temperatures above +30 °C

**Additional details:**

- bracket series: page 89
- brakes: page 112–113
- wheel series: page 60
- bearing types: page 84–85



2



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LWKX-TPA 101G-PX25	LWKX-TPA 101G-FI-PX25	100	32	100	plain bore	138	90 x 66	75 x 45 / 61 x 51	8.5	38
LWKX-TPA 101XKF-PX25	LWKX-TPA 101XKF-FI-PX25	100	32	100	ball bearing (C)	138	90 x 66	75 x 45 / 61 x 51	8.5	38
LWKX-TPA 126G-PX25	LWKX-TPA 126G-FI-PX25	125	32	110	plain bore	163	90 x 66	75 x 45 / 61 x 51	8.5	40
LWKX-TPA 126XKF-PX25	LWKX-TPA 126XKF-FI-PX25	125	32	110	ball bearing (C)	163	90 x 66	75 x 45 / 61 x 51	8.5	40

### Versions / options



	plain bore version	electrically conductive version, non-marking, grey	with plate size 90x66 mm 75x50 mm	in special colour
Technical description page		50	106	
<b>Product code suffix</b>		<b>LWKXE-...-ELS</b>	<b>-PX26</b>	
Available for		all ball bearing versions*	upon request**	upon request

\* Load capacity of electrically conductive version reduced by 35%  
 \*\* In accordance with DIN 18867-8 (large-scale catering equipment)