

LER-VE series

Pressed steel castors with bolt hole, wheel with standard solid rubber tyre



50–205 kg

Bracket: LER series


- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: VE series

- tyre: standard solid rubber, hardness 80 Shore A, colour black
- rim: pressed steel, zinc-plated, blue-passivated, Cr6-free

Additional details:

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 195
- bearing types: page 84–85



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LER-VE 80R	LER-VE 80R-FI	80	25	50	roller bearing	102	70	13	38
LER-VE 100R	LER-VE 100R-FI	100	30	70	roller bearing	125	70	13	36
LER-VE 125R	LER-VE 125R-FI	125	37.5	100	roller bearing	150	70	13	38
LER-VE 150R	LER-VE 150R-FI	150	40	135	roller bearing	190	88	13	54
LER-VE 160R	LER-VE 160R-FI	160	40	135	roller bearing	195	88	13	54
LER-VE 180R	LER-VE 180R-FI	180	50	170	roller bearing	215	88	13	54
LER-VE 200R	LER-VE 200R-FI	200	50	205	roller bearing	235	88	13	54

Versions / options



	with non-marking grey tyre	electrically conductive version, black tyre	with thread guard, pressed steel, zinc-plated	with steel foot guard	truck lock
Technical description page	52	50	116	116	114
Product code suffix	-SG	-EL	-FA	-FS	FF 100-1 / FF 125-1
Available for	all	all	all	upon request	wheel Ø 100+125 mm