

## L-ALEV, B-ALEV, BH-ALEV series

Pressed steel castors, medium-duty version, with top plate, wheel with "Blickle EasyRoll" elastic solid rubber tyres



200–500 kg

**Bracket:** L/B/BH series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**

- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 150 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** ALEV series


- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: die-cast aluminium

**Additional details:**

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 221
- bearing types: page 84–85



3



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-ALEV 100K	B-ALEV 100K	L-ALEV 100K-FI	100	40	200	ball bearing	125	100 x 85	80 x 60	9	36
L-ALEV 125K	B-ALEV 125K	L-ALEV 125K-FI	125	40	250	ball bearing	150	100 x 85	80 x 60	9	38
L-ALEV 150K	B-ALEV 150K	L-ALEV 150K-FI	150	50	400	ball bearing	190	140 x 110	105 x 75–80	11	60
L-ALEV 161K	B-ALEV 161K	L-ALEV 161K-FI	160	40	300	ball bearing	195	140 x 110	105 x 75–80	11	60
L-ALEV 160K	B-ALEV 160K	L-ALEV 160K-FI	160	50	400	ball bearing	195	140 x 110	105 x 75–80	11	60
L-ALEV 180K	B-ALEV 180K	L-ALEV 180K-FI	180	50	400	ball bearing	215	140 x 110	105 x 75–80	11	60
L-ALEV 200K	B-ALEV 200K	L-ALEV 200K-FI	200	50	400	ball bearing	235	140 x 110	105 x 75–80	11	65
L-ALEV 250K-3	BH-ALEV 250K	*	250	50	500	ball bearing	295	140 x 110	105 x 75–80	11	77

\* "stop-top" brake version, see versions / options

### Versions / options



	with non-marking grey tyre	antistatic version, non-marking, grey tyre	electrically conductive version, black tyre	with "stop-top" brake	with "central-stop" central brake system	with directional lock (separate) 1x 360°	with steel foot guard
Technical description page	52	53	50	112	113	115	116
<b>Product code suffix</b>	<b>-SG</b>	<b>-SG-AS</b>	<b>-EL</b>	<b>-ST</b>	<b>-CS11</b>	<b>see **</b>	<b>-FS</b>
Available for	all	wheel Ø 100, 125x40, 160x50, 200, 250 mm	wheel Ø 100, 125, 160, 200, 250 mm	all	wheel Ø 160+200 mm	for wheel Ø and plate dimensions, see**	all

\*\* RI-03.01 for wheel Ø 100–125 mm, RI-05.03 for wheel Ø 150–200 mm (Only for swivel castors without brake or swivel castor with "stop-top" and "central-stop" brake upon request)