

# LH-SETH, BH-SETH series

Pressed steel castors, heavy-duty design, with top plate, wheel with Blickle Extrathane® polyurethane tread

## 凸 500-900 kg

#### Bracket: LH/BH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- Swivel bracket:
- · double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to four specially-shaped, hardened bearing seats

#### Wheel: SETH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown, non-marking, non-staining
   wheel centre: thick-walled pressed steel, triple
- wheel centre: thick-walled pressed steel, triple welded, with tubular steel hub, lacquered, colour silver

### Additional details:

- bracket series: page 92
- brakes: page 112–113
   wheel agricul page 292
- wheel series: page 282
- bearing types: page 84–85














Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LH-SETH 125K	BH-SETH 125K	LH-SETH 125K-FI	125	50	500	ball bearing	170	140 x 110	105 x 75-80	11	55
LH-SETH 150K	BH-SETH 150K	LH-SETH 150K-FI	150	50	650	ball bearing	197	140 x 110	105 x 75-80	11	65
LH-SETH 160K	BH-SETH 160K	LH-SETH 160K-FI	160	50	700	ball bearing	202	140 x 110	105 x 75-80	11	65
LH-SETH 200K	BH-SETH 200K	LH-SETH 200K-FI	200	50	900	ball bearing	245	140 x 110	105 x 75–80	11	70
LH-SETH 250K	BH-SETH 250K	*	250	60	900	ball bearing	295	140 x 110	105 x 75-80	11	82

<sup>\* &</sup>quot;stop-top" brake version, see versions / options



				A STATE OF THE PARTY OF THE PAR		
	with "stop-top" brake	with "ideal-stop" brake total height +17 mm	directional lock (sepa- rate) 1 x 360°	with steel foot guard	truck lock	
Technical description page	112	112	115	116	114	
Product code suffix	-ST	-IS	RI-05.03	-FS	FF 125 / 150 / 160 / 200	
Available for	all	wheel Ø 160– 200 mm**	wheel Ø 125– 200 mm***	all	wheel Ø 125-200 mm	

<sup>\*\*</sup> Synthetic adapter plate to balance out total height for swivel and fixed castors without "ideal-stop" brake: product code AP3-17

<sup>\*\*\*</sup> Only for swivel castors without brake or swivel castor with "stop-top" brake upon request